

MOTOTRBO™ SL2M

INSTANT COMMUNICATION,
PROFESSIONAL STYLE



GENERAL SPECIFICATIONS		
Model Number	SL2M	
Band	VHF	UHF
Frequency	136-174 MHz	403-470 MHz
High Power Output (Digital)	3 W	
High Power Output (Analog)	2 W	
Low Power Output	0.5, 1W	
Channel Spacing	12.5, 25kHz	
Channel Capacity	256	
Dimensions (H x W x D), Radio + Standard Battery	125.7 x 55.0 x 22.7 mm	
Weight, Radio + Standard Battery	190g	
FCC Description	-	-
IC Description	-	-
Digital / Analog Battery Life ¹ (Li-Ion (2300mAh) Battery)	13.5 / 11 hrs	
Power Supply (Nominal)	3.7 V	

TRANSMITTER SPECIFICATIONS	
4FSK Digital Modulation	12.5 kHz Data: 7K60F1D and 7K60FXD
	12.5 kHz Voice: 7K60F1E and 7K60FXE
	Combination of 12.5 kHz Voice and Data: 7K60F1W
Digital Protocol	ETSI TS 102 361-1, -2, -3
Conducted/Radiated Emissions (TIA603D)	-36 dBm < 1GHz, -30 dBm > 1GHz
Adjacent Channel Power	60dB (12.5 kHz channel), 70dB (25 kHz channel)
Frequency Stability	± 0.5 ppm

ADDITIONAL FEATURES

- Transmit Interrupt
- Enhanced Privacy
- Fixed Privacy Key Decryption
- Bluetooth Audio
- Bluetooth Data
- Indoor Location
- Intelligent Audio
- Mute Mode
- Noise Suppressor
- Quick Text Messaging

RECEIVER SPECIFICATIONS	
Analog Sensitivity (12dB SINAD)	0.3 uV, 0.22uV (typical)
Digital Sensitivity (5% BER)	0.25 uV, 0.19uV (typical)
Intermodulation (TIA603D)	70 dB
Adjacent Channel Selectivity, (TIA603A)-1-tone	60 dB (12.5 kHz channel), 70 dB (25 kHz channel)
Adjacent Channel Selectivity, (TIA603D)-2-tone	45 dB (12.5 kHz channel), 70 dB (25 kHz channel)
Spurious Rejection (TIA603D)	70 dB

TT6 Tam Đảo, Quận 10, Tp.Hồ Chí Minh
19LK3, 90 Nguyễn Tuấn, Thanh Xuân, HN
(+84-28) 3862 4466/ (+84-24) 6282 5919
www.thekjsc.vn info@thekjsc.vn

CENTURY telecom



AUDIO SPECIFICATIONS

Digital Vocoder Type	AMBE+2™
Audio Response	TIA603D
Rated Audio	0.5 W
Audio Distortion at Rated Audio	5% (3% typical)
Hum and Noise	-40 dB (12.5 kHz channel) -45 dB (25 kHz channel)
Conducted Spurious Emissions (TIA603D)	-57 dBm

BLUETOOTH SPECIFICATIONS

Version	4
Range	Class 2, 33 ft (10 m)
Supported Profiles	Bluetooth Headset Profile (HSP), Serial Port Profile (SPP), Motorola fast push-to-talk.
Simultaneous Connections	1 x audio accessory and 1 x data device
Permanent Discoverable Mode	Optional

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature ²	-22 F to 140 F (-30 C to +60 C)
Storage Temperature	-40 F to 185 F (-40 C to +85 C)
Electrostatic Discharge	IEC 61000-4-2 Level 3
Dust and Water Intrusion	IEC 60529 - IP54
Packaging Test	MIL-STD 810D and E

WiFi SPECIFICATIONS

Standards Supported	IEEE 802.11b, 802.11g, 802.11n
Security Protocol Supported	WPA, WPA-2, WEP
Maximum Number of SSIDs	128

MILITARY STANDARDS

	810C		810D		810E		810F		810G	
Applicable MIL-STD	Methods	Procedures	Methods	Procedures	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.5	I/A1, II/A1
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temperature Shock	503.1	I	503.2	A1/C3	503.3	A1/C3	503.4	I	503.5	I-C
Solar Radiation	505.1	II	505.2	I/Hot-Dry	505.3	I/Hot-Dry	505.4	I/Hot-Dry	505.5	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Humidity	507.1	II	507.2	II/Hot-Humid	507.3	II/Hot-Humid	507.4	-	507.5	II - Aggravated
Salt fog	509.1	I	509.2	I	509.3	I	509.4	-	509.5	-
Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Sand	-	-	510.2	II	510.3	II	510.4	II	510.5	II
Vibration	514.2	VIII/CatF/ CurveW, XI	514.3	I/Cat10, II/Cat3	514.4	I/Cat10, II/Cat3	514.5	I/Cat24, II/Cat5	514.6	I/Cat24, II/Cat5
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.6	I, IV, V, VI

1: Typical battery life, 5/5/90 profile at maximum transmitter power with Bluetooth and Wi-Fi disabled. Actual observed runtimes may vary.

2: Radio only. Operating temperature specification for a Li-Ion battery is -10 °C to +60 °C. Specifications subject to change without notice.

All specifications shown are typical values

For more information, please visit us on the web at:

www.motorolasolutions.com/MOTOTRBO

or contact us at

VIỄN THÔNG THỂ KỸ - PHÂN PHỐI VÀ TTDV BẢO HÀNH BỘ ĐÀM MOTOROLA



TT6 Tam Đảo, Quận 10, Tp.Hồ Chí Minh
19LK3, 90 Nguyễn Tuấn, Thanh Xuân, HN



HCM: (+84-28) 3862 4466
HN: (+84-24) 6282 5919



www.thevjsc.vn



info@thevjsc.vn

Motorola Solutions Singapore Pte Ltd

80 Pasir Panjang Road #18-81 Mapletree Business City Singapore 117372

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylised M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2017 Motorola, Inc. All rights reserved.

SL2M_DS_AP_051017